



## Shandong Yochi Bearing Co., Ltd.



0.5 Inch | 12.7 Millimeter x 1.125 Inch | 28.58  
Millimeter x 1.188 Inch | 30.175 Millimeter  
TIMKEN VAS 1/2 Pillow Block Bearings

Bearing No. VAS 1/2

VAS 1/2 Bearing 2D drawings and 3D CAD models

Category	Pillow Block Bearings
Inventory	0.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	0.45
EAN	0087796056350
Product Group	M06110
Number of Mounting Holes	2
Mounting Method	Eccentric Collar
Housing Style	2 Bolt Pillow Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	3/8 Inch
Relubricatable	Yes
Insert Part Number	GRA008RRB
Seals	Double Land Riding Rubber Contact
Housing Configuration	1 Piece Solid
Inch - Metric	Inch
Other Features	Single Row   Spherical   Normal Duty   High Base   With Set Screw
Long Description	2 Bolt Pillow Block; 1/2" Bore; 1-3/16" Base to Center Height; Eccentric Collar



## Shandong Yochi Bearing Co., Ltd.

	Mount; Ball Bearing; Relubricatable; Cast Iron; Double Land Riding Rubber Contact; Non- expansion
Category	Pillow Block
UNSPSC	31171511
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Pillow Block
Manufacturer URL	<a href="http://www.timken.com">http://www.timken.com</a>
Manufacturer Item Number	VAS 1/2
Weight / LBS	1
B	1.188 Inch   30.175 Millimeter
d	0.5 Inch   12.7 Millimeter
Actual Bolt Center to Center	3.6 Inch   92Millimeter
Bolt Spacing Maximum	0 Inch   0Millimeter
Nominal Bolt Center to Center	3.6 Inch   92 Millimeter
D	1.125 Inch   28.58 Millimeter
Bolt Spacing Minimum	0 Inch   0Millimeter
Shaft Size d	1/2 in
Bearing Type	Ball Bearing
Inside Ring Outside Diameter	0.531 in
Dimension T	0.594 in
Series	Standard
Weight	1.001 lb
Seal Type	Molded Shroud
Base to Center Height H	30.16 mm
Total Length L	123.8 mm
Total Width A	1.189 in



## Shandong Yochi Bearing Co., Ltd.

Bolt Hole Spacing J	92.1 mm
Bolt Hole Width N	11.1 mm
Bolt Hole Length N1	22.2 mm
Foot Height H1	11.9 mm
Total Height H2	56.4 mm
Dimension L1	41.3 mm
Inside Ring Width B	=Bearings1_Inside Ring Width= mm
Center of Bearing from End S	6.4 mm
Dimension B1	1.126 in
Static Load Rating	1070 lbf
Dynamic Load Rating	2380 lbf